High Current Power Inductor
CSQA3218LP Series

Construction Wire

Outline:
- Low loss,small magnetostriction coefficient result in low noise.
- Flat wire winding, achieving very low DC resistance.
- The inductance value and DC bias characteristic are little affected by temperature.
- Magnetically shielded structure, excellent resistance to electromagnetic interference.
- Compact design saves PCB mounting area.

Features:
- Core material: Composite.
- Environmental: RoHS compliant, halogen free.
- Weight: 73.0g
- Moisture Sensitivity: Level (MSL) 1 (Unlimited floor life at <30°C / 85% relative humidity)
- Operating temperature range: -55℃ ~ +155℃ (Including coil's temperature rise).
- Storage temperature range: -55℃ ~ +155℃

Application:
- PV inverter/Industrial control/New energy
- DC /DC converters/Motherboards/Filter
- High current switching regulators

1 Product Dimensions (mm)



※ Date code will be changed by manufacture date



Schematic



Reference Land Pattern

2 Electrical Characteristics

Part No.	Inductance (μH)※1	D.C.R. (mΩ)		Isat (A)※2	Irms (A)※3
	±20%	Typical	Max.	Typical	Typical
CSQA3218LP-3R6MC	3.60	0.50	0.60	70.0	75.0
CSQA3218LP-5R1MC	5.10	0.65	0.75	58.0	67.0
CSQA3218LP-7R5MC	7.50	1.00	1.20	50.0	56.0
CSQA3218LP-100MC	10.0	1.40	1.70	43.0	48.0
CSQA3218LP-130MC	13.0	1.80	2.15	35.0	43.0
CSQA3218LP-180MC	18.0	2.20	2.65	32.0	38.0
CSQA3218LP-220MC	22.0	2.80	3.35	30.0	32.0
CSQA3218LP-270MC	27.0	3.60	4.30	26.0	28.5

All data is tested on 25℃ ambient temperature

1. Inductance measure condition at 100kHz,0.1V.
2. Isat: the actual value of DC current when the Inductance decrease 30% of its initial Value.
3. Irms: The actual value of DC current when the Temperature rise is ΔT50℃(Ta=25℃)

3 How to Order

CSQA3218LP-3R6MC

Model
Dimensions
Value Code
Coating

CODACA ELECTRONIC CO., LTD

TEL: +86 755 89585372 FAX: +86 755 89585280
http://www.codaca.com E-mail: info@codaca.com

This product is not authorized for use in any application related to safety.
Specification subject to change without notice. Please check website for latest information.

Revised: 09/20/2024

4 Saturation Current vs Temperature Rise Current Curve

















5 L vs Frequency

CSQA3218LP-3R6MC



CSQA3218LP-5R1MC



CSQA3218LP-7R5MC



CSQA3218LP-100MC



CSQA3218LP-130MC



CSQA3218LP-180MC



CSQA3218LP-220MC



CSQA3218LP-270MC



6 Impedance vs Frequency

CSQA3218LP-3R6MC



CSQA3218LP-5R1MC



CSQA3218LP-7R5MC



CSQA3218LP-100MC



CSQA3218LP-130MC



CSQA3218LP-180MC



CSQA3218LP-220MC



CSQA3218LP-270MC



7 Packing Specification

7.1 Plastic Tray Dimensions (mm)





Packaging Unit (Pcs)	Material
12	APET

L typ	W typ	H typ	No. of Tray (Pcs)	Packaging Unit(Pcs)	Material
265	205	32	1	12	Paper

7.2 Packing(mm)



L typ	W typ	H typ	No. of Inner Carton(Pcs)	Packaging Unit(Pcs)	Material
275	232	261	7	84	Paper

8 Soldering Specification

8.1 Reflow Profile for SMT Components



8.2 Classification of Peak Package Body Temperature (T_P)

	Package Thickness	Package Volume		
		<350 mm^3	350 ~ 2000 mm^3	>2000 mm^3
PB-Free Assembly	<1.6mm	260℃	260℃	260℃
	1.6 ~ 2.5mm	260℃	250℃	245℃
	≥2.5mm	250℃	245℃	245℃

※ Reflow is referred to standard IPC/JEDEC J-STD-020E.

9 Notice of Use

9.1 Special remind:Circuit design, component placement, PCB size and thickness, cooling system and etc. all will affect the product temperature. Please verify the product temperature in the final application.

9.2 Product in packing storage condition:temperature 5～40℃, RH≤70%.
If taking out for use, the remaining products should be sealed in plastic bags and preserved in accordance with the above conditions, to avoid oxidation of terminals (electrodes), affecting soldering status.

9.3 A storage of Codaca Electronic products for longer than 12 months is not recommended, Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.

9.4 Do not keep products in unsuitable storage conditions, such as areas susceptible to high temperatures, high humidity, dust or corrosion.

9.5 Always handle products with care.

9.6 Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering. Always ensure optimum conditions for soldering.

9.7 When this product will be used on a similar or new project to the original one, sometimes it might be unable to satisfy the specifications due to different condition of usage.

9.8 This inductor itself does not have any protective function in abnormal condition, such as overload, short-circuit, open-circuit conditions, etc. Therefore, it shall be confirmed that there is no risk of smoke, fire, dielectric withstand voltage, insulation resistance, etc., or use in abnormal conditions protective devicesor protection circuit in the end product.

9.9 Hi-Pot test with higher voltage than spec value will damage insulating material and shorten its life.

9.10 If using in potting compound, the magnet wire coating might be damaged, please consult with us.

9.11 Refrain from rinsing coils. If necessary, please consult with us.

*9.12 Codaca Electronic products without "V" prefix are qualified for industrial product requirement , and with "V" prefix are qualified for AEC-Q200, but it doesn't mean that Codaca Electronic products can absolutely meet specific industry norms and quality test standards in automotive electronics or more strict application fields . Codaca Electronic will be exempted from being responsible for the consequences of using Codaca products in automotive electronic or higher application field related to safety when without being aware of it.