



Outline:

- Magnetic shielded structure, excellent resistance to electro magnetic interference (EMI).
- Flat wire winding, achieve a low DC resistance.

Features:

- Core material: Lead product.
- Core and winding loss:
- Environmental: RoHS, Reach compliant, Halogen free
- Weight: 12.24 g
- Moisture Sensitivity: Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity).
- Operating temperature range: -55°C ~ +165°C (including coil's self temperature rise)
- Storage temperature range: -55°C ~ +165°C

Application:

- Circuit / Buck circuit.
- DC/DC Converter / LED driver.
- Lights/Car BMS/ Car electric/motor controller.

1 Electrical Characteristics

Part No.	Inductance (μH) $\times 1$	D.C.R. (m Ω)		Isat (A)		Irms (A)	
		Typical	Max.	10%drop 30%drop	$\times 2$	Typical	$\times 3$
CSUS1514-R25N	0.25 $\pm 30\%$	1.10	1.30	65.00	28.00		
CSUS1514-R60N	0.60 $\pm 30\%$	1.50	1.80	47.00	24.00		
CSUS1514-1R1N	1.10 $\pm 30\%$	1.90	2.20	35.00	21.50		
CSUS1514-1R8M	1.80 $\pm 20\%$	2.30	2.70	27.00	19.80		
CSUS1514-2R6M	2.60 $\pm 20\%$	2.60	3.10	22.50	18.00		
CSUS1514-3R6M	3.60 $\pm 20\%$	3.00	3.60	19.60	16.80		
CSUS1514-4R7M	4.70 $\pm 20\%$	3.50	4.20	17.30	15.80		
CSUS1514-6R8M	6.80 $\pm 20\%$	3.80	4.60	15.00	14.90		
CSUS1514-7R6M	7.60 $\pm 20\%$	4.20	5.00	13.40	14.20		
CSUS1514-100M	10.0 $\pm 20\%$	4.60	5.50	11.50	13.80		
CSUS1514-120M	12.0 $\pm 20\%$	5.00	6.00	10.90	13.10		
CSUS1514-130M	13.0 $\pm 20\%$	5.40	6.50	10.00	12.70		
CSUS1514-150M	15.0 $\pm 20\%$	6.70	8.00	9.44	11.40		
CSUS1514-180M	18.0 $\pm 20\%$	7.20	8.60	8.80	10.90		
CSUS1514-220M	22.0 $\pm 20\%$	8.70	10.40	8.25	9.90		
CSUS1514-270M	27.0 $\pm 20\%$	10.90	13.10	7.29	8.90		
CSUS1514-330M	33.0 $\pm 20\%$	12.90	15.50	6.50	8.10		
CSUS1514-470M	47.0 $\pm 20\%$	18.90	22.70	5.43	6.70		
CSUS1514-560M	56.0 $\pm 20\%$	22.40	26.90	4.80	6.20		
CSUS1514-680M	68.0 $\pm 20\%$	25.40	30.50	4.50	5.80		
CSUS1514-820M	82.0 $\pm 20\%$	32.80	39.40	4.00	5.10		
CSUS1514-101L	100.0 $\pm 15\%$	40.00	48.00	3.40	4.63		
CSUS1514-151L	150.0 $\pm 15\%$	63.40	76.10	2.95	3.63		
CSUS1514-221L	220.0 $\pm 15\%$	98.90	118.70	2.48	2.90		


All data is tested on 25°C ambient temperature

$\times 1$. Inductance measure condition at 100kHz, 0.1V


$\times 2$. Saturation current : the actual value of DC current when the inductance decrease 10% and 30% of its initial value.

$\times 3$. Irms: the actual value of DC current when the temperature rise is $\Delta T 40^\circ\text{C}$ ($T_a = 25^\circ\text{C}$)
















2 Product Dimensions (mm)












3 How to Order




4 Saturation Current vs Temperature Rise Current Curve






5 Inductance vs Frequency Curve


CSUS1514-R25N




CSUS1514-R60N




CSUS1514-1R1N




CSUS1514-1R8M




CSUS1514-2R6M




CSUS1514-3R6M




CSUS1514-4R7M




CSUS1514-6R8M




CSUS1514-7R6M




CSUS1514-100M




CSUS1514-120M




CSUS1514-130M




CSUS1514-150M




CSUS1514-180M




CSUS1514-220M




CSUS1514-270M




CSUS1514-330M




CSUS1514-470M




CSUS1514-560M




CSUS1514-680M




CSUS1514-820M




CSUS1514-101L



CSUS1514-151L




CSUS1514-221L




6 Impedance vs Frequency Curve


CSUS1514-R25N




CSUS1514-R60N




CSUS1514-1R1N




CSUS1514-1R8M




CSUS1514-2R6M




CSUS1514-3R6M




CSUS1514-4R7M




CSUS1514-6R8M




CSUS1514-7R6M




CSUS1514-100M




CSUS1514-120M




CSUS1514-130M




CSUS1514-150M




CSUS1514-180M




CSUS1514-220M




CSUS1514-270M




CSUS1514-330M




CSUS1514-470M




CSUS1514-560M




CSUS1514-680M




CSUS1514-820M




CSUS1514-101L



CSUS1514-151L




CSUS1514-221L




7 Packing Specification

7.1 Carrier Tape Dimensions (mm)



※ Packing is referred to the international standard IEC 60286-3.

7.2 Reel Dimensions (mm)



7.3 Carton Dimensions and Packing Quantity


■ Inner Carton : 340×340×95mm

■ Out Carton : 360×360×370mm

Product Series	Quantity / Reel	Inner Carton Quantity	Out Carton Quantity
CSUS1514-Series	150pcs	(150×2) = 300pcs	(300×3) = 900pcs

8 Soldering Specification

8.1 Reflow Profile for SMT Components



8.2 Classification of Peak Package Body Temperature (T_p)

	Package Thickness	Package Volume		
		<350 mm ³	350 ~ 2000 mm ³	>2000 mm ³
PB-Free Assembly	<1.6mm	260°C	260°C	260°C
	1.6 ~ 2.5mm	260°C	250°C	245°C
	≥2.5mm	250°C	245°C	245°C

※ Reflow is referred to standard IPC/JEDEC J-STD-020E.

9 Notice of Use

- 9.1 Special remind:Circuit design, component placement, PCB size and thickness, cooling system and etc. all will affect the product temperature. Please verify the product temperature in the final application.
- 9.2 Product in packing storage condition:temperature 5 ~ 40°C, RH≤ 70%.
If taking out for use, the remaining products should be sealed in plastic bags and preserved in accordance with the above conditions, to avoid oxidation of terminals (electrodes), affecting soldering status.
- 9.3 A storage of Codaca Electronic products for longer than 12 months is not recommended, Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- 9.4 Do not keep products in unsuitable storage conditions, such as areas susceptible to high temperatures, high humidity, dust or corrosion.
- 9.5 Always handle products with care.
- 9.6 Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering.
Always ensure optimum conditions for soldering.
- 9.7 When this product will be used on a similar or new project to the original one,
sometimes it might be unable to satisfy the specifications due to different condition of usage.
- 9.8 This inductor itself does not have any protective function in abnormal condition, such as overload, short-circuit, open-circuit conditions, etc. Therefore, it shall be confirmed that there is no risk of smoke, fire, dielectric withstand voltage, insulation resistance, etc., or use in abnormal conditions protective devices or protection circuit in the end product.
- 9.9 Hi-Pot test with higher voltage than spec value will damage insulating material and shorten its life.
- 9.10 If using in potting compound, the magnet wire coating might be damaged, please consult with us.
- 9.11 Refrain from rinsing coils. If necessary, please consult with us.
- 9.12 Codaca Electronic products without "V" prefix are qualified for industrial product requirement , and with "V" prefix are qualified for AEC-Q200, but it doesn't mean that Codaca Electronic products can absolutely meet specific industry norms and quality test standards in automotive electronics or more strict application fields . Codaca Electronic will be exempted from being responsible for the consequences of using Codaca products in automotive electronic or higher application field related to safety when without being aware of it.