CODΔ**C**Δ



1 Product Dimensions (mm)



Outline:

- High frequency low loss magnetic core material
- Low cost, high reliability
- For high frequency noise suppression

Features:

- Core material: Ferrite
- Environmental: RoHS, Reach compliant ,Halogen free
- Weight: RHR354508-450 (0.50g)
 RHR356508-700 (0.65g)
 RHR356508-700 (0.70m)
- RHR359008-950 (0.70g) Moisture Sensitivity: Level (MSL) 1
- (unlimited floor life at <30°C / 85% relative humidity)
 Operating temperature range: -40°C~+85°C
- (including coil's self temperature rise)
 Storage temperature range: -40°C~+85°C

- Application:
- Widely used in VGA card, EGA card, mother board, TV game

| Part No. | ΦA (mm) | D (mm) | d (mm) | F (mm) | H (mm) | H0 (mm) | E (mm) |
|---------------|-----------|-----------|-----------|---------|----------|-----------|---------|
| RHR354508-450 | 3.50±0.30 | 4.50±0.30 | 0.65±0.05 | 5.0±0.5 | 32.5Max. | 19.5±1.00 | 1.0Ref. |
| RHR356508-700 | 3.50±0.30 | 6.50±0.30 | 0.65±0.05 | 5.0±0.5 | 32.5Max. | 19.5±1.00 | 1.0Ref. |
| RHR359008-950 | 3.50±0.30 | 9.00±0.30 | 0.65±0.05 | 5.0±0.5 | 32.5Max. | 16.5±1.00 | 1.0Ref. |

ΦA

2 Reference Hole Pattern (mm)



3 Schematic



4 Electrical Characteristics

| Part No. | Impec) ۲) ** | dance 2) 1 | D.C.R. (mΩ) | Rated Current (A) ※2 | Hi-pot (Vdc) | Insulation Resistance (ΜΩ) |
|---------------|--------------------|------------------|----------------|----------------------------|-----------------|----------------------------------|
| | Min. | | Max. | Max. | 2mA 3S | Min. |
| RHR354508-450 | 30.0 | 45.0 | 10.0 | 7.00 | 500 | 100 |
| RHR356508-700 | 40.0 | 70.0 | 10.0 | 7.00 | 500 | 100 |
| RHR359008-950 | 60.0 | 95.0 | 10.0 | 7.00 | 500 | 100 |

All data is tested on 25°C ambient temperature

%1 Impedance measure condition at 25MHz,0.05V,100MHz,0.05V.

×2 Rated current: the actual value of DC current when the temperature rise is Δ T40°C(Ta=25°C). TEL: +86 755 89585372

CODACA ELECTRONIC CO., LTD

This product is not authorized for use in any application related to safety. Specification subject to change without notice. Please check web site for latest information. http://www.codaca.com

FAX: +86 755 89585280

E-mail: info@codaca.com



5 Packing Specification

5.1 Taping dimensions (mm)



5.2 Packing(mm)



| Part No. | Quantity / Carton | No. of Inner Carton | Packaging Unit | Material |
|---------------|-------------------|---------------------|----------------|----------|
| RHR354508-450 | 2000 Pcs | 10 Pcs | 20000 Pcs | Paper |
| RHR356508-700 | 2000 Pcs | 10 Pcs | 20000 Pcs | Paper |
| RHR359008-950 | 2000 Pcs | 10 Pcs | 20000 Pcs | Paper |

CODACA ELECTRONIC CO., LTD

TEL: +86 755 89585372 FAX: http://www.codaca.com E-mai

FAX: +86 755 89585280 E-mail: info@codaca.com

This product is not authorized for use in any application related to safety. Specification subject to change without notice. Please check web site for latest information.



6 Soldering Specification

6.1 Wave soldering temperature curve



6.2 Classification Wave Soldering Profile:

| Profile Feature | | Pb-Free Assembly | Sn-Pb Assembly |
|---------------------------------------|------------|---|---|
| Preheat Temperature Min | Ts min | 100 °C | 100 °C |
| Preheat Temperature Typical | Ts typical | 120 °C | 120 °C |
| Preheat Temperature Max | Ts max | 130 °C | 130 °C |
| Preheat Time ts from Ts min to Ts max | ts | 70 seconds | 70 seconds |
| Ramp-up Rate | ΔΤ | 150 °C max. | 150 °C max. |
| Peak Temperature | Тр | 250 °C - 260 °C | 235 °C - 260 °C |
| Time of actual peak temperature | tp | max. 10 seconds max. 5 seconds each wave | max. 10 seconds max. 5 seconds each wave |
| Ramp-down Rate, Min | | ~ 2 K/ second | ~ 2 K/ second |
| Ramp-down Rate, Typical | | ~ 3.5 K/ second | ~ 3.5 K/ second |
| Ramp-down Rate, Max | | ~ 5 K/ second | ~ 5 K/ second |
| Time 25 °C to 25 °C | | 4 minutes | 4 minutes |

% Wave Soldering is refer to standard EN61760-1:2006.

```
CODACA ELECTRONIC CO., LTD
```

TEL: +86 755 89585372 FAX: +8 http://www.codaca.com E-mail:

FAX: +86 755 89585280 E-mail: info@codaca.com

This product is not authorized for use in any application related to safety. Specification subject to change without notice. Please check web site for latest information.



7 Notice of Use

- 7.1 Special remind:Circuit design, component placement, PCB size and thickness, cooling system and etc. all will affect the product temperature. Please verify the product temperature in the final application.
- 7.2 Product in packing storage condition:temperature 5~40°C, RH≤70%.
 If taking out for use, the remaining products should be sealed in plastic bags and preserved in accordance with the above conditions, to avoid oxidation of terminals (electrodes), affecting soldering status.
- 7.3 A storage of Codaca Electronic products for longer than 12 months is not recommended, Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- 7.4 Do not keep products in unsuitable storage conditions, such as areas susceptible to high temperatures, high humidity, dust or corrosion.
- 7.5 Always handle products with care.
- 7.6 Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering. Always ensure optimum conditions for soldering.
- 7.7 When this product will be used on a similar or new project to the original one, sometimes it might be unable to satisfy the specifications due to different condition of usage.
- 7.8 This inductor itself does not have any protective function in abnormal condition, such as overload, short-circuit, open-circuit conditions, etc. Therefore, it shall be confirmed that there is no risk of smoke, fire, dielectric withstand voltage, insulation resistance, etc., or use in abnormal conditions protective devicesor protection circuit in the end product.
- 7.9 Hi-Pot test with higher voltage than spec value will damage insulating material and shorten its life.
- 7.10 If using in potting compound, the magnet wire coating might be damaged, please consult with us.
- 7.11 Refrain from rinsing coils. If necessary, please consult with us.
- *7.12Codaca Electronic products without "V" prefix are qualified for industrial product requirement, and with "V" prefix are qualified for AEC-Q200, but it doesn't mean that Codaca Electronic products can absolutely meet specific industry norms and quality test standards in automotive electronics or more strict application fields. Codaca Electronic will be exempted from being responsible for the consequences of using Codaca products in automotive electronic or higher application field related to safety when without being aware of it.

CODACA ELECTRONIC CO., LTD

 TEL: +86 755 89585372
 FAX: +86 755 89585280

 http://www.codaca.com
 E-mail: info@codaca.com