



Outline:

- Symmetrical air gap structure design, better DC bias capability.
- Flat wire winding with good heat dissipation and low temperature rise.
- Closed magnetic circuit, reducing electromagnetic radiation and conduction interference to improve electromagnetic compatibility(EMC).

Features:

- Environmental: RoHS compliant, halogen free.
- Weight: 41.60 g~42.88 g
- Moisture Sensitivity: Level (MSL) 1
(Unlimited floor life at <30°C / 85% relative humidity)
- Operating temperature range: -55°C~+155°C
(Including coil's temperature rise).
- Storage temperature range: -55°C~+155°C
- AEC-Q200 qualified.





Application:

- Ideally used in server application
- High current power supplies, battery power devices
- DC/DC converters in distributed power systems

Construction Wire




1 Product Dimensions (mm)



※ Date code will be changed by manufacture date.

2 Electrical Characteristics

Part No.	Inductance (μH)※1 ±15%	D.C.R. (mΩ)		Isat (A)※2 Typical	Irms (A)※3 Typical
		Typical	Max.		
VSCFA2918L-1R8LC	1.80	0.75	0.90	120	42.0
VSCFA2918L-2R7LC	2.70	1.10	1.32	100	36.0
VSCFA2918L-3R9LC	3.90	1.50	1.80	85.0	32.0
VSCFA2918L-5R1LC	5.10	2.20	2.64	75.0	30.0
VSCFA2918L-6R8LC	6.80	2.80	3.36	65.0	22.0
VSCFA2918L-8R6LC	8.60	2.80	3.36	50.0	22.0
VSCFA2918L-110LC	11.0	3.40	4.08	45.0	21.0
VSCFA2918L-150LC	15.0	4.10	4.92	36.0	19.0
VSCFA2918L-170LC	17.0	5.30	6.36	34.0	16.0
VSCFA2918L-200LC	20.0	6.50	7.80	32.0	14.0



Reference Land Pattern


Schematic

All data is tested on 25°C ambient temperature









1. Inductance measure condition at 100kHz, 0.1V.
2. Isat: the actual value of DC current when the Inductance decrease 20% of its initial Value.
3. Irms: the actual value of DC current when the Temperature rise is ΔT40°C(Ta=25°C)



3 How to Order

VSCFA 2918L-2R0 L C









4 Saturation Current vs Temperature Rise Current Curve







5 L vs Frequency




VSCFA2918L-110LC




VSCFA2918L-150LC



VSCFA2918L-170LC




VSCFA2918L-200LC




6 Impedance vs Frequency


VSCFA2918L-1R8LC




VSCFA2918L-2R7LC









VSCFA2918L-3R9LC




VSCFA2918L-5R1LC





7 Packing Specification


7.1 Plastic Tray Dimensions (mm)



Packaging Unit (Pcs)	Material
20	APET

L typ	W typ	H typ	No. of Tray (Pcs)	Packaging Unit(Pcs)	Material
265	205	30	1	20	Paper


7.2 Packing(mm)



L typ	W typ	H typ	No. of Inner Carton	Packaging Unit(Pcs)	Material
275	232	261	8	160	Paper

8 Soldering Specification

8.1 Reflow profile for SMT components



8.2 Classification of peak package body temperature (Tp)

	Package Thickness	Package Volume		
		<350 mm ³	350-2000 mm ³	>2000 mm ³
PB-Free Assembly	<1.6mm	260°C	260°C	260°C
	1.6 mm - 2.5 mm	260°C	250°C	245°C
	>2.5mm	250°C	245°C	245°C

※ Reflow is referred to standard IPC/JEDEC J-STD-020E.

9 Notice of Use

- 9.1 Special remind: Circuit design, component placement, PCB size and thickness, cooling system and etc. all will affect the product temperature. Please verify the product temperature in the final application.
- 9.2 Product in packing storage condition: temperature 5~40°C, RH≤70%.
If taking out for use, the remaining products should be sealed in plastic bags and preserved in accordance with the above conditions, to avoid oxidation of terminals (electrodes), affecting soldering status.
- 9.3 A storage of Codaca Electronic products for longer than 12 months is not recommended, Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- 9.4 Do not keep products in unsuitable storage conditions, such as areas susceptible to high temperatures, high humidity, dust or corrosion.
- 9.5 Always handle products with care.
- 9.6 Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering.
Always ensure optimum conditions for soldering.
- 9.7 When this product will be used on a similar or new project to the original one,
sometimes it might be unable to satisfy the specifications due to different condition of usage.
- 9.8 This inductor itself does not have any protective function in abnormal condition, such as overload, short-circuit, open-circuit conditions, etc. Therefore, it shall be confirmed that there is no risk of smoke, fire, dielectric withstand voltage, insulation resistance, etc., or use in abnormal conditions protective devices or protection circuit in the end product.
- 9.9 Hi-Pot test with higher voltage than spec value will damage insulating material and shorten its life.
- 9.10 If using in potting compound, the magnet wire coating might be damaged, please consult with us.
- 9.11 Refrain from rinsing product. If necessary, please consult with us.
- *9.12 Codaca Electronic products without "V" prefix are qualified for industrial product requirement , and with "V" prefix are qualified for AEC-Q200, but it doesn't mean that Codaca Electronic products can absolutely meet specific industry norms and quality test standards in automotive electronics or more strict application fields . Codaca Electronic will be exempted from being responsible for the consequences of using Codaca products in automotive electronic or higher application field related to safety when without being aware of it.