

Outline:

- Magnetic shielded structure, metal shielding cover with strong EMI resistance.
- Auxiliary terminals effectively improve vibration resistance and enhance welding stability.
- Compact design saves PCB mounting area.
- High inductance, high current.
- Wide temperature and low power consumption material, low core loss.


Features:

- Core material: Composite.
- Core and winding loss:
www.codaca.com/DesignTool_Power-Inductor-Loss-Comparison.html
- Environmental: RoHS compliant, halogen free.
- Weight: 36.16g
- Moisture Sensitivity: Level (MSL) 1
(Unlimited floor life at <math><30^{\circ}\text{C}</math> / 85% relative humidity)
- Operating temperature range: (Including coil's temperature rise).
- Storage temperature range:

Application:

- Storage inductor for high efficiency DC/DC converters with high ripple currents.
- Resonant SMPS.
- Filter for audio applications.

1 Product Dimensions (mm)



| Inductance | 22.0 μH | 33.0 μH -68.0 μH | 100 μH | 150 μH -220 μH |
|------------|--------------------|--|-------------------|--------------------------------------|
| A(mm) | 1.5 | 1.3 | 1.0 | 0.9 |
| B(mm) | 1.8 | 1.6 | 1.3 | 1.2 |

※ Date code will be changed by manufacture date.

2 Electrical Characteristics


| Part No. | Inductance (μH)※1 $\pm 20\%$ | D.C.R. (m Ω) | | Isat (A)※2 Typical | Irms (A)※3 Typical |
|-----------------|---|----------------------|-------|--------------------------|--------------------------|
| | | Typical | Max. | | |
| CPCF2920AS-220M | 22.0 | 4.90 | 5.39 | 16.0 | 24.05 |
| CPCF2920AS-330M | 33.0 | 6.90 | 7.59 | 12.5 | 20.05 |
| CPCF2920AS-470M | 47.0 | 8.80 | 9.68 | 11.0 | 17.50 |
| CPCF2920AS-680M | 68.0 | 10.30 | 11.33 | 8.50 | 16.00 |
| CPCF2920AS-101M | 100.0 | 22.90 | 25.19 | 9.00 | 10.50 |
| CPCF2920AS-151M | 150.0 | 30.60 | 33.66 | 6.70 | 9.00 |
| CPCF2920AS-221M | 220.0 | 36.45 | 40.10 | 5.20 | 8.15 |

All data is tested on 25°C ambient temperature








1. Inductance measure condition at 100kHz, 0.1V.
2. Isat: the actual value of DC current when the Inductance decrease 20% of its initial Value.
3. Irms: The actual value of DC current when the Temperature rise is $\Delta T 40^{\circ}\text{C}$ ($T_a = 25^{\circ}\text{C}$)

3 How to Order

CPCF2920AS-220M




4 Saturation Current vs Temperature Rise Current Curve




5 L vs Frequency


CPCF2920AS-220M




CPCF2920AS-330M




CPCF2920AS-470M




CPCF2920AS-680M




CPCF2920AS-101M



CPCF2920AS-151M




CPCF2920AS-221M




6 Impedance vs Frequency


CPCF2920AS-220M




CPCF2920AS-330M




CPCF2920AS-470M




CPCF2920AS-680M




CPCF2920AS-101M



CPCF2920AS-151M




CPCF2920AS-221M



7 Packing Specification


7.1 Plastic Tray Dimensions (mm)



| Packaging Unit (Pcs) | Material |
|----------------------|----------|
| 20 | APET |

| L typ | W typ | H typ | No. of Tray (Pcs) | Packaging Unit(Pcs) | Material |
|-------|-------|-------|-------------------|---------------------|----------|
| 265 | 205 | 34 | 1 | 20 | Paper |

7.2 Packing(mm)



| L typ | W typ | H typ | No. of Inner Carton | Packaging Unit(Pcs) | Material |
|-------|-------|-------|---------------------|----------------------|----------|
| 275 | 232 | 261 | 7 | 140 | Paper |

8 Notice of Use

- 8.1 Special remind:Circuit design, component placement, PCB size and thickness, cooling system and etc. all will affect the product temperature. Please verify the product temperature in the final application.
- 8.2 Product in packing storage condition:temperature 5~40°C, RH≤70%.
If taking out for use, the remaining products should be sealed in plastic bags and preserved in accordance with the above conditions, to avoid oxidation of terminals (electrodes), affecting soldering status.
- 8.3 A storage of Codaca Electronic products for longer than 12 months is not recommended, Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- 8.4 Do not keep products in unsuitable storage conditions, such as areas susceptible to high temperatures, high humidity, dust or corrosion.
- 8.5 Always handle products with care.
- 8.6 Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering.
Always ensure optimum conditions for soldering.
- 8.7 When this product will be used on a similar or new project to the original one,
sometimes it might be unable to satisfy the specifications due to different condition of usage.
- 8.8 This inductor itself does not have any protective function in abnormal condition, such as overload, short-circuit, open-circuit conditions, etc. Therefore, it shall be confirmed that there is no risk of smoke, fire, dielectric withstand voltage, insulation resistance, etc., or use in abnormal conditions protective devices or protection circuit in the end product.
- 8.9 Hi-Pot test with higher voltage than spec value will damage insulating material and shorten its life.
- 8.10 If using in potting compound, the magnet wire coating might be damaged, please consult with us.
- 8.11 Refrain from rinsing coils. If necessary, please consult with us.
- * 8.12 Codaca Electronic products without "V" prefix are qualified for industrial product requirement , and with "V" prefix are qualified for AEC-Q200, but it doesn't mean that Codaca Electronic products can absolutely meet specific industry norms and quality test standards in automotive electronics or more strict application fields . Codaca Electronic will be exempted from being responsible for the consequences of using Codaca products in automotive electronic or higher application field related to safety when without being aware of it.